

HMT130 Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	Price
Vaisala HUMICAP® Temperature Transmitter		HMT130	T					A	0							
Output parameters		Temperature output only														
Transmitter type		Wall mount/fixed probe														
		<i>Remote probe with 3 m cable</i>														
		<i>Remote probe with 5 m cable</i>														
		<i>Remote probe with 10 m cable</i>														
		<i>Remote probe with 10 m cable + 10 m extension</i>														
		<i>Remote probe with 20 m cable</i>														
Display		No display														
		<i>Display</i>														
Analog output signal (RS485 also included)		0...1 V														
		3-wire														
		0...5 V														
		3-wire														
		0...10 V														
		3-wire														
SPECIAL		Define scale: 3-wire _____ V *)														
Parameter for Output 1		T														
		-40...+60 °C (-40...+140 °F)														
		-20...+80 °C (-4...+176 °F)														
		0...+60 °C (+32...+140 °F)														
		-40...+80 °C (-40...+176 °F)														
		0...+50 °C (+32...+122 °F)														
SPECIAL		Define quantity _____ Scale _____														
Parameter for Output 2		None														
Display Units		Metric														
		Non metric														
Sensor protection		Plastic grid														
		Plastic grid with PTFE filter														
		Stainless steel sintered filter (for remote probes only)														
Transmitter installation		No accessories														
		<i>Rain shield with installation kit (215109)</i>														
Installation kit for probe		No accessories														
		<i>Duct installation kit (215619)</i>														
		<i>Probe mounting flange (226061)</i>														
		<i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i>														
		<i>Probe mounting clamp, 1 piece (225501)</i>														
Cable bushings		Cable gland for 2...6 mm diameter cable														
		Conduit fitting PG9														
		Conduit fitting NPT 1/2"														
		No bushing (rubber plug)														
		<i>All bushings (includes A, B, C and D)</i>														
PC Accessories		No														
		<i>Service cable for PC, USB (219685)</i>														
Operation manual		No manual														
		Multilingual														
Total																
QTY																
Total value																

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130 | T A 1 D B A 0 1 A 1 1 A 0 Z